

ID Material: 3
Rble: R. Antich
Revision: 5
Date: 06/09/2016

HDS57

Description

HDS57 is a rigid woven friction material with a medium friction coefficient. HDS57 is the Sauleda heavy duty material for clutches. Developed in 1997, manufactured with draft yarn and aramid fibres. It is recommended for commercial vehicles, especially when thermal conditions are high.

Material table

Fiction properties

Dynamic Friction Coefficient (@79N, 7m/s):	0.42±0.05	μ
Wear Rate (@79N, 7m/s):	40±10	mm ³ /Kwh
T° Fading (@100N, 11.5m/s):	280±10	°C

Physical properties

Hardness (DIN53505):	80±5	Shore-D
Specific Gravity (ASTM D792-91):	1.7±0.05	gr/cm ³
Ignition Loss (ASTM D-2524):	50±2	%
Acetone Extraction ISO2859-1:	2±0.2	%

Mechanical properties

Compressive Strength (UNE 53205):	120±5	N/mm ²
Burst Resistant (200 x 137 x 3,5)@200°C:	12000±100	RPM

Recommended Working Values

T° Max. Continuous Operation:	250	°C
T° Max. Intermittent Operation:	350	°C

Material type : Woven yarn

Appearance



Formats



Applications

Heavy vehicle clutches - Trucks clutches - Vehicles clutches -

Price Level : € € €

Reach (EC)1907/2006 - RoHS 2011/65/EU : Compliance

Others

Recommended Mating Surface: Perlitic cast iron, hardness HB150-200

Recommended Adhesives: Thermosetting adhesive

